



## RESILON POLYMERS PVT. LTD.

### Certificate of Analysis

Product RAYLON 66

Grade 66R33GF

Color NATURAL

Lot No.

Date

#### Description: -

This is to certify that above material is tested as per the given details and the results are recorded as under.

Properties	Test Condition	Test Method	Unit	Typical Value	Tolerance	Result
<strong>Physical</strong>						
Specific Gravity		ASTM D792	-	1.37	+/-0.02	1.38
Melt Flow Rate	275° C/2.16Kg	ASTM D1238	g/10min	15	+/-5	18
Ash Content		ASTM D5630	%	33	+/-3	34.0
<strong>Mechanical</strong>						
Tensile Strength@yield	50mm/min	ASTM D638	Mpa	190	+/-15	195
Tensile Elongation@Break	50mm/min	ASTM D638	%	4	+/-1	4
Flexural Modulus	2mm/min	ASTM D790	Mpa	8500	+/-300	8720
Flexural Strength	2mm/min	ASTM D790	Mpa	280	+/-15	283
Izod Impact 3.2 mm Notched	23°C	ASTM D256	Kg cm/cm	10	+/-2	11
<strong>Thermal</strong>						
Heat Deflection Temperature (annealed)	1.80 Mpa	ASTM D648	°C	240	+/-10	241

Note: - Properties measured at DAM conditions.

This is system generated report, hence no signature is required.